

water at its finest



Convenience...eliminate the need, the cost and the hassle of bottled water! 1,500 one gallon water bottles will end up in your recycle bin for every one FM DWS 1500 filter replacement. That's 300 five-gallon delivered bottles in and out of your home! And there is no deposit required!

- Provides fresher tasting water, coffee and beverages
- Advanced filtration and contaminant adsorption system reduces sediment, chlorine taste and odor, lead and parasitic protozoan cysts that may be present in the water supply
- Sanitary Quick Change filter cartridges for easy installation and service — no spills, no mess
- Compact, integral design eliminates costly plumbing components and fittings for an economical installation and long-term, hassle-free maintenance
- 1/4 turn quick-change filter design
- NSF Certified and listed for contaminant reduction



Advanced contaminant adsorption technology

Exclusive quick change filter design

FM DWS 1500 Drinking Water System

Drinking Water System



advantages OF THE FM DWS 1500 SYSTEM



- Conveniently dispenses filtered water for all water-based cooking and consumption
- Sanitary Quick Change System
 - clean filter replacement eliminates handling filter media
 - as easy to change as a light bulb
- Capable of providing filtered water to multiple water-using appliances
 - kitchen and bar sinks, lavatory, hot-water dispensers and refrigerator/icemakers (with proper fittings, not supplied)
- The FM DWS 1500 reduces
 - sediment
 - chlorine taste and odor
 - lead
 - cyst
 - asbestos

RELATIVE COST PER GALLON OF WATER

Water Cooler	Bottled Water	Pour Through Pitcher	Filter in Faucet	3M Water Filters
\$\$\$	\$\$\$\$	\$	\$	\$
<ul style="list-style-type: none"> • Expensive • Heavy 5 gallon bottles weigh 40 lbs (18.1 kg). Risk of injury and spills • Water delivery — by homeowner or more often by diesel engine (leaded fuel) trucks • Storage required for both full and empty bottles • Awkward placement. Clash with high-style decorative kitchen designs • Often requires electricity • Limited usage — not practical for food preparation • Cannot supply other water using appliances 	<ul style="list-style-type: none"> • Expensive • Heavy and cumbersome • Difficult to transport • Requires frequent trips to market • Storage space required • Limited usage — not practical for food preparation • Cannot supply other water using appliances • Bottled water not necessarily "safer" than ordinary tap water¹ <p>¹ National Resources Defense Council (NRDC)</p>	<ul style="list-style-type: none"> • Frequent filter replacements with yearly costs above \$75¹ • Limited volume — complaints of constant filling which can take up to 20 minutes • Pitcher requires continuous cleaning, takes up space on counter or inside refrigerator • Limited usage — not practical for food preparation/cooking due to limited capacity • Clogs easily — even slower drip filtration plus shorter filter life • Cannot supply other water using appliances <p>¹ Consumer Reports, Aug 2000</p>	<ul style="list-style-type: none"> • Frequent filter replacements with yearly costs above \$90¹ • Short filter life: 200 gallons (757 liters) • Awkward styling: low decorative appeal • Lower flow rates (0.5 gpm/1.89 lpm) than faucet mount styles • Clogs easily — even slower flow rates with shorter filter life • Cannot supply other water using appliances <p>¹ Consumer Reports, Aug 2000</p>	<ul style="list-style-type: none"> • 1,500 gallon (5,678 liter) filter life • One filter change per year: low maintenance • Easy filter replacement: no tools required • Separate faucet dispenses filtered water on demand • Lead, asbestos and cyst reduction health-related claim, verified by third-party regulatory agency

WARNING: To reduce the risk associated with the ingestion of contaminants:
 • Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. EPA Establishment #070595-CT-001



System tested and certified by NSF International against NSF/ANSI Standards 42 and 53 for the reduction of the claims specified on the Performance Data Sheet.

CAUTION: To reduce the risk associated with property damage due to water leakage:

- Read and follow Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- **Protect from freezing**, remove filter cartridge when temperatures are expected to drop below 40°F (4.4°C).
- **Do not install on hot water supply lines.** The maximum operating water temperature of this filter system is 100°F (37.8°C).
- **Do not install** if water pressure exceeds 125 psi (862 kPa). If your water pressure exceeds 80 psi (552 kPa), you must install a pressure limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.
- **Do not install** where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- The disposable filter cartridge **MUST** be replaced every 12 months, at the rated capacity or if a noticeable reduction in flow rate occurs.



CUNO Incorporated
 400 Research Parkway
 Meriden, CT 06450, U.S.A.
 Toll Free: 1.800.733.1199
 203.237.5541